



ARTEL

www.rrpelletkachel.nl













**Nu Continu
Pellet aanvoer**



Pelletkachel

Milano*Next*



MILANO NEXT		8 KW		10 KW	
	Eenheid	Max.	Min.	Max.	Min.
 Continu	Omw/min.	2700	630	2700	630
 POWER Vermogen	kW	7,48	2,64	10,10	2.5
 Rendement	%	92,6	91	92,7	89,53
 Afvoer Diam.	mm	Ø 50		Ø 80	
 Inlaat Diam.	mm	Ø 50		Ø 50	
 Pellettank Inh.	kg	13		13	
 Pellet diameter	mm	Ø 6		Ø 6	
 Verbruik / uur	kg/h	1,68	0,5	2,6	0,6
 Branduren/tank	h	11	7,73	22	6,5
 Oppervlakte	m ²	1* 60		1* 70	
 Gewicht	kg	80		90	
 Wi Fi READY	Optie	Ja		Ja	
Afmeting	HxBxD	865x440x440		955x440x440	
Keramische gloeikaars		Ja		Ja	
Branderkamer		Gietijzer		Gietijzer	
Uitvoering		Open toestel		Open toestel	
Afvoer		Achter		Achter	

1* Verwarmbaar volume is gebaseerd op een redelijk tot goed geïsoleerde woning met standaard kamerhoogte van ± 260 cm.