

Charlton & Jenrick^{LTD}

Best of British fires, fireplaces & stoves

PUREVISION

Technische data van de nieuwe serie “PVR” ronde modellen.

Model	Purevision PVR 5kW	Purevision PVR 5Kw with Heat Exchanger
Appliance weight (packed/unpacked) (Kg):	105/94	105/94
Approximate Output Range: (kW)	3.2 – 6.8	3.2 – 6.8
Harmonised EN European Standard (hEN):	EN13240: 2001 Amd 2: 2004	EN13240: 2001 Amd 2: 2004
Performance Characteristics using Wood Fuel		
Total Efficiency: (%)	76,8	83,9
Declared nominal output: (kW)	5	5
Mean C _n H _m emission (@13% O ₂): (Nmg/m ³)	45	52
Mean NO _x emission (@13% O ₂): (Nmg/m ³)	86	89
DIN+ particulates (@13% O ₂): (Nmg/m ³)	13	13
PD6434 Particulate Emissions High output: (gh ⁻¹)	2,3	2,3
PD6434 Particulate Emissions Low output: (gh ⁻¹)	1,5	1,5
Optical Density Time > 0.2 High (Mins)	0	0
Optical Density Time > 0.2 Low (Mins)	0,2	0,2
Approximate Max Log Length: (mm)	300	300
Performance Characteristics using Maxibrite Briquetted Smokeless Fuel		
Total Efficiency: (%):	81,8	87,2
Declared nominal output: (kW)	5	5
Mean C _n H _m emission (@13% O ₂): (Nmg/m ³)	22	15
Mean NO _x emission (@13% O ₂): (Nmg/m ³)	105	124
DIN+ particulates (@13% O ₂): (Nmg/m ³)	20	25
Safety Distances From Combustibles		
Side Wall: (mm)	400/600	400/600
Rear Wall: (mm)	175/70	175/70

